# LPCB®

www.redbooklive.com

## Certificate of Product Approval

Certificate Number: 1000g

lssue: 01

PRE

## **Burton Safes Limited**

Units 20 – 28 Brockholes Business Park Rock Mill Road Brockholes Holmfirth HD9 7BN

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

### Product

Ajax SR3 modular security cages

### Standard

LPS 1175: Issue 6

Requirements and testing procedures for the LPCB approval and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities



© BRE Global Ltd, 2014

## LPCB®

## Appendix to Certificate No: 1000g Burton Safes Limited

## Issue: 01

### Modular Security Cages

Product	Туре	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Security	LPCB Ref.
Name		Height (m)	Height (m)	Width (m)	Width (m)	Length (m)	Length (m)	Rating	No.
Ajax SR3	Modular cage formed from Ajax SR3 fixed and opening grilles <sup>1</sup>	0.715	3.67 <sup>3,4</sup>	0.48	Unlimited <sup>2,5</sup>	1.0	Unlimited <sup>2,5</sup>	3	1000g/01

### **System Components**

Component Type	Minimum Height (m)	Maximum Height (m)	Minimum Width (m)	Maximum Width (m)	Minimum Length (m)	Maximum Length (m)
Wall panel <sup>4</sup>	0.625	3.58	0.3	3.06	N/A	N/A
Roof panel	N/A	N/A	0.3	3.06	0.625	3.0
Doorset <sup>6</sup>	0.625	2.7	1.0	3.025	N/A	N/A

#### Notes:

1. Cages are rectilinear in plan and not limited to a simple rectangle. That is approval covers cages with acute and obtuse vertical corners.

2. The maximum sizes of the cage are subject to specific assessment of physical restrictions and operational conditions.

3. The maximum height of any opening sash within the cage is 2.7 m. Cages above this height incorporate a fixed grille.

4. Wall panels can be coupled vertically to form cage height.

5. The maximum clear span is 4 m. Spans greater than this require support column(s).

6. For details of locking options and accessories approved refer to certificate 1000f.

7. The certification covers the installation of the cage directly to a concrete floor<sup>8</sup>.

8. The cages can also be secured onto raised floors. This is providing the cage extends under the raised floor to a concrete floor beneath it. The wall panels located under the raised floor shall be bolted to the underside of the wall panels located above the floor, sandwiching the floor panels between them. The wall panels located under the raised floor shall also be directly fixed to the concrete floor beneath the cage.

This certificate and appendix is maintained and held in force through regular surveillance activities

P. Dillo	Paul Dillon	23 May 2017	23 May 20			
Signed for LPCB	Verifier	Date of Issue	Date of First	ssue		
TON CERTIFICATION	This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit <u>www.redbooklive.com/terms)</u> .					
	To check the validity of this certificat www.redbooklive.com/check, scan t		bco			
	LPCB is part of BRE Global Ltd., Gars T: +44 (0)333 321 8811 F: +44 (0)19	ton, Watford WD25 9XX. 923 664603 E: <u>Enquiries@breglobal.com</u>		DIE		



© BRE Global Ltd, 2014